16:08

MAT-8072US

- 4 -

## REMARKS

Applicants acknowledge with thanks the courtesy extended to their representative by Examiner Taylor during the personal interview of October 2, 2002.

As a result of the personal interview, Applicants have amended the claims as indicated above. The purpose of these amendments is to clarify that the caller information which is stored in the memory is in fact transmitted caller information and not caller information manually input using, for example, a keyboard.

Allowance of the above-identified application is respectfully requested.

Respectfully Submitted,

KatnerPrestia

Lawrence E. Ashery, Reg. No. 34,515

Attorney for Applicants

LEA:kc

Enclosure:

Version With Markings Showing Changes Made

Dated: November 8, 2002

Suite 301, One Westlakes, Berwyn P.O. Box 980 Valley Forge, PA 19482-0980

(610) 407-0700

The Assistant Commissioner for Patents is hereby authorized to charge payment to Deposit Account No. **18-0350** of any fees associated with this communication.

I hereby certify that this correspondence is being facsimile transmitted to the United States Patent end Trademark Office (Fax No. (703) 872-9314) on the date shown below.

Nøyember 8, 2002

## VERSION WITH MARKINGS SHOWING CHANGES MADE

## IN THE CLAIMS:

1	(Twice Amended) A telephone apparatus comprising:
2	an information detector for detecting transmitted caller information
3	from a telephone line,
4	an operation unit for specifying caller group information which
5	relates to the <u>transmitted</u> caller information,
6	a memory for storing the transmitted caller information and related
7	caller group information,
8	a display unit, and
9	a controller, said controller displays the caller information in said
10	display unit, and searches said memory, and when the transmitted received caller
11	information coincides with caller information in the memory, , the caller group
12	information which relates to the transmitted caller information is identified and
13	displayed.
	E CONTRACTOR OF THE CONTRACTOR
1	<ol><li>(Twice Amended) A telephone apparatus comprising:</li></ol>
2	an information detector for detecting transmitted caller information
3	from a telephone line,
4	an operation unit for registration of caller group information which
5	relates to the <u>transmitted</u> caller information,
6	a memory for storing the transmitted caller information and related
7	caller group information,
8	a display unit,
9	a light source for emitting a plurality of color lights for illuminating
10	said display unit, and

MAT-8072US

- 6 **-**

11	a controller for controlling said light source,
12	wherein said light source emits a first color light when the caller
13	information detected by said information detector coincides with the caller
14	information stored in said memory and said controller causes the identification
15	and display of said caller group information, and said light source emits a second
16	color light when the caller information detected by said information detector does
17	not coincide with caller information stored in said memory .
1	6. (Twice Amended) A telephone apparatus comprising:
2	a plurality of sub units,
3	an information detector for detecting transmitted caller information
4	from a telephone line,
_	<u>.</u>
5	a caller information memory for storing the <u>transmitted</u> caller
6	information detected by said information detector,
7	a response information memory for storing the sub unit information
8	of the sub unit answering the call and the transmitted caller information detected
9	by said information detector,
10	a sub unit specifying caller information memory for storing the sub
11	unit information and the caller information detected by said information detector
12	when the answering sub unit specifies, and
13	a controller,
14	wherein said controller, when detecting that the caller information
15	stored in said sub unit specifying caller information memory coincides with the
16	caller information detected by said information detector, calls a sub unit
17	corresponding to the sub unit information being read out from said sub unit
18	specifying caller information memory.
	•